

Nano^oBasic Roll

Primer for roller application

Product Description

Nano^oBasic Roll is a water based primer for wood and parquet floors, with a suitable viscosity for roller application. *Nano^oBasic Roll* dries very quickly, is simple to sand off between applications, gives good coverage and a smooth floor surface. NMP-free. For indoor use only.

Preparation

Sand the floor down to bare wood. Final sanding must be carried out using sandpaper of no. 120 grit. The floor must be free from contamination and dust. Any polish or grease residues must be very carefully removed.

Application

Shake the container well, and allow the bubbles formed to disperse before application. *Nano^oBasic Roll* should be at room temperature before application. The floor temperature must be hold between + 13°C and +30°C. Ideal conditions are a floor temperature of +20°C and relative humidity of 55%. In doubt of appearance prime a small sample area. The smallest recommended total quantity of primer applied is 0,1 litre per m². Sand off after priming with screen no. 120 grit and vacuum carefully. Allow *Nano^oBasic Roll* to dry entirely (the floor colour has evened out), and then apply at least two coats of *Nano^oAvenue*, *Nano^oElite*, *Nano^oClassic* or *Nano^oStrada* floor finish.

Cleaning

Clean brushes and other tools with water before the primer has had time to dry.

Health and Safety

Nano^oBasic Roll is not classified under the C.H.I.P. regulations. Use the normal care due when handling chemical products. Ensure good ventilation. Use protective goggles and gloves if there is any risk of splashing. If the product comes into contact with your skin, wash it off with soap and water. If the product gets into your eyes, rinse with a generous amount of water. For further information see Material Safety Data Sheet.

Technical Service

Please contact the Nanosol Technical Service at phone no. +46 303 56 329, or your local agent.

Technical Data

Contents:	Acrylate hybrid, NMP-free
Viscosity: (FC 4, 20°C)	19 seconds
Solids content:	App. 40%
Density:	1.1 kg/litre
Application:	1 litre covers 8 m ² per coat
Drying time:	20-60 min
Storage:	12 months in unopened package at +5°C to +30°C. Protect from frost. Keep out of the reach of children.
Package:	5 litre plastic containers
Art No:	01.3005

This Nanosol Product Sheet is intended for advice only. The values apply to normal conditions, which can of course vary due to means of application, temperature etc. We retain the right to make changes and amendments without prior notice.