

NanoCentic 2

Maintenance Oil

NanoCentic 2 Natur - NanoCentic 2 White

Product description

NanoCentic 2 is oxidative hardening maintenance oil for periodic maintenance of oiled wood and parquet surfaces. For indoor use only. Not suitable for maintenance of 2K oiled floors or hardwaxed floors. **NanoCentic 2** has a convenient smell and does only contain solvents with no labelling requirements. Once the floor has dried, it does not release emissions. In combination with the floor oil **NanoMillic Comfort**, **NanoCentic 2** is the heavy traffic oil system for wood floors in all areas.

Preparation

Remove loose particles, which otherwise could damage the surface by dry cleaning the floor. If necessary, remove marks, see separate instructions.

Frequency of maintenance

Generally the maintenance frequency is determined of the kind of wear out on the floor. Every maintenance treatment done with **NanoCentic 2** increases the mechanical strength of the oiled floor.

If an oiled floor has become grey and matt, it is in the need of maintenance.

On heavy traffic areas, maintenance treatment should be carried out more often when the floor is young, before it is worn out too badly. Early maintenance treatment increases the lifetime of the floor.

In domestic areas, maintenance should be carried out only if it appears necessary.

Application

For water free **maintaining and cleaning** of a soiled floor, apply **NanoCentic 2** and work in the oil using a red polishing pad. If this does not remove the dirt, try using a green, brown or black pad. On extremely dirty floors a 80 grit sanding screen can be used. Collect the excess oil and remove it. Finally polish the surface using a white superpad and some fresh **NanoCentic 2** until no more spots or smears appear round the pad. Wait over night or at least 3 hours before stepping on the floor.

NanoCentic 2 can be used to improve the result of the base treatment of a floor while it is oiled for the first time with **NanoMillic Comfort** floor oil. While doing the final polishing with the white pad, moisten the pad with **NanoCentic 2** and polish without leaving spots or smears. For best protection of the floor, accomplish another treatment with **NanoCentic 2** within 2-3 weeks after base treatment.

Cleaning

Tools can be cleaned using white spirit.

Health and Safety

NanoCentic 2 is not classified under the C.H.I.P. regulations. Use the normal care due when handling chemical products. Ensure good ventilation. Use protective goggles and gloves if there is any risk of splashing. If the product comes into contact with your skin, wash it off with soap and water. If the product gets into your eyes, rinse with a generous amount of water. For further information see Material Safety Data Sheet.

Technical Service

If you have any questions please contact Nanosol Technical Service on telephone +46 303 56 329, or your local agent.

Technical data

Contents: Urethane-modified fatty acid
n-paraffin hydrocarbons

Quantity required: 1 litre for 40-80 m²,
depending on type of wood

Working temp.: +15-25°C

Drying time: 3-8 hours

Storage: best before 2 years at max 25°C in
unopened container.

When the container is opened the
content might start hardening when
it's stored a longer time.

Keep out of the reach of children.

Package: 5l metal can (art 02.1305)
6x1l plastic can (Art 02.1301)

This Nanosol Product Sheet is intended for advice only. The numbers apply to normal conditions, which may vary due to means of application, temperature etc. We retain the right to make changes and amendments without prior notice.