

NanoTone

waterborne floor stain

Product Description

NanoTone floor stain is a waterborne stain for colouring of untreated or bare wood sanded wood and parquet floors.

NanoTone floor stain is available in a large number of popular shades (see colour sheet) and is used to enhance or change the colour of a floor. For indoor use only.

Preparation

Before staining, the floor must be sanded with a flatbed sander and sandpaper of no. 120 grit. Sand the floor down to bare wood. It is important that the entire floor is evenly sanded. The floor must be free from contamination and dust.

Application

Shake or stir up carefully. Apply a **NanoTone** richly on a 30 to 50 cm wide strip on the floor, following the direction of the wood. Use a sponge or rubber squeegee. Then work the stain in with an absorbent, lint-free rag at the same time as you dry off any surplus. To avoid overlapping marks, always leave the leading edge wet. Apply the next strip of **NanoTone** and work over the stain within 5 minutes on overlaps, to dissolve the earlier strip. After drying off, the floor should be virtually dry. Wait until the next day before applying Nanosol top lacquers or oils. NOTE! Before applying a top lacquer, one layer of the primer **NanoBasic Roll** must be applied.

Cleaning

Before the stain has dried, clean brushes and other tools with water.

Health and Safety

NanoTone is not classified under the C.H.I.P. regulations. Use the normal care due when handling chemical products. Ensure good ventilation. Use protective goggles and gloves if there is any risk of splashing. If the product comes into contact with your skin, wash it off with soap and water. If the product gets into your eyes, rinse with a generous amount of water. For further information see Safety Data Sheet.

Technical Service

Please contact the Nanosol Technical Service at phone no. +46 303 56 329, or your local agent.

Technical Data

Binder:	Water
Application:	Pine: 1 litre covers approx. 10 m ² Oak: 1 litre covers approx. 20 m ²
Open time:	Approx. 5 minutes
Storage:	12 months in unopened package at +5°C to +30°C. Protect from frost. Keep out of the reach of children.
Package:	1 litre plastic cans

Shades

- White
- Mahogany
- Brown
- Diluter (to enlighten the colour)
- Cherry
- Golden Brown
- Black

All shades can be mixed together. To get a lighter colour, mix with **NanoTone Diluter**.

NOTES:

- Never apply more than one layer of stain. The result would be cloudy.
- To extend the open time (time the stain can be worked with once applied on the floor) in bad circumstances (high sucking wood or low humidity in the air, add 5 – 10% of NanoExtender (does not work in Tone black!).
- Oak floors coloured with Tone white can not be sealed with any top lacquer because of yellow miss colourings. Those floors can be treated with Millic Comfort floor oil.
- Areas larger than 20 square meter should be worked with at least 2 workers to avoid drying marks.

This Nanosol Product Sheet is intended for advice only. The values apply to normal conditions, which can of course vary due to means of application, temperature etc. We retain the right to make changes and amendments without prior notice.